



830 Planning Schedule with Release Capability

X12/V4010/830 : 830 Planning Schedule with Release Capability

Version: 1.2

Created:	8/8/2022
Modified:	10/23/2023

Table of Contents

Planning Schedule with Release Capability.....	1
Transaction Set Header	2
Beginning Segment for Planning Schedule	3
Loop Name	4
Name	5
Additional Name Information	6
Address Information	7
Geographic Location	8
Loop Item Identification	9
Item Identification	10
Unit Detail	12
Loop Ship/Delivery Pattern.....	13
Ship/Delivery Pattern	14
Forecast Schedule	15
Loop Shipped/Received Information	16
Shipped/Received Information.....	17
Transaction Totals	18
Transaction Set Trailer	19
EDI Sample	20

830

Planning Schedule with Release Capability

Functional Group=PS

Purpose: This Draft Standard for Trial Use contains the format and establishes the data contents of the Planning Schedule with Release Capability Transaction Set (830) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide for customary and established business practice relative to the transfer of forecasting/material release information between organizations. The planning schedule transaction may be used in various ways or in a combination of ways, such as: (1) a simple forecast; (2) a forecast with the buyer's authorization for the seller to commit to resources, such as labor or material; (3) a forecast that is also used as an order release mechanism, containing such elements as resource authorizations, period-to-date cumulative quantities, and specific ship/delivery patterns for requirements that have been represented in "buckets," such as weekly, monthly, or quarterly. The order release forecast may also contain all data related to purchase orders, as required, because the order release capability eliminates the need for discrete generation of purchase orders.

Heading:

Pos	Id	Segment Name	Req	Max Use	Repeat	Notes	Usage
010	ST	Transaction Set Header	M	1			Must use
020	BFR	Beginning Segment for Planning Schedule	M	1			Must use
<u>LOOP ID - N1</u>					<u>200</u>		
230	N1	Name	O	1			Used
240	N2	Additional Name Information	O	2			Used
250	N3	Address Information	O	2			Used
260	N4	Geographic Location	O	1			Used

Detail:

Pos	Id	Segment Name	Req	Max Use	Repeat	Notes	Usage
<u>LOOP ID - LIN</u>					<u>>1</u>		
010	LIN	Item Identification	M	1			Must use
020	UIT	Unit Detail	O	1			Used
<u>LOOP ID - SDP</u>					<u>260</u>		
450	SDP	Ship/Delivery Pattern	O	1			Used
460	FST	Forecast Schedule	O	260			Used
<u>LOOP ID - SHP</u>					<u>25</u>		
470	SHP	Shipped/Received Information	O	1			Used

Summary:

Pos	Id	Segment Name	Req	Max Use	Repeat	Notes	Usage
010	CTT	Transaction Totals	O	1		N3/010	Used
020	SE	Transaction Set Trailer	M	1			Must use

Notes:

3/010 Number of line items (CTT01) is the accumulation of the number of LIN segments. If used, hash total (CTT02) is the sum of the values of the quantities (FST01) for each FST segment.

ST**Transaction Set Header**

Pos: 010	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use**Purpose:** To indicate the start of a transaction set and to assign a control number**Element Summary:**

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	Transaction Set Identifier Code	M	ID	3/3	Must use
Description: Code uniquely identifying a Transaction Set All valid standard codes are used. (Total Codes: 298)						
ST02	329	Transaction Set Control Number	M	AN	4/9	Must use
Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set						

Semantics:

1. The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

BFR Beginning Segment for Planning Schedule

Pos: 020	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 8

User Option (Usage): Must use

Purpose: To indicate the beginning of a planning schedule transaction set; whether a ship or delivery based forecast; and related forecast envelope dates

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BFR01	353	Transaction Set Purpose Code	M	ID	2/2	Must use
		Description: Code identifying purpose of transaction set All valid standard codes are used. (Total Codes: 65)				
BFR02	127	Reference Identification	X	AN	1/30	Used
		Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier				
BFR03	328	Release Number	X	AN	1/30	Used
		Description: Number identifying a release against a Purchase Order previously placed by the parties involved in the transaction				
BFR04	675	Schedule Type Qualifier	M	ID	2/2	Must use
		Description: Code identifying the type of dates used when defining a shipping or delivery time in a schedule or forecast All valid standard codes are used. (Total Codes: 11)				
BFR05	676	Schedule Quantity Qualifier	M	ID	1/1	Must use
		Description: Code identifying the type of quantities used when defining a schedule or forecast All valid standard codes are used. (Total Codes: 4)				
BFR06	373	Date	M	DT	8/8	Must use
		Description: Date expressed as CCYYMMDD				
BFR07	373	Date	O	DT	8/8	Used
		Description: Date expressed as CCYYMMDD				
BFR08	373	Date	M	DT	8/8	Must use
		Description: Date expressed as CCYYMMDD				

Syntax Rules:

1. R0203 - At least one of BFR02 or BFR03 is required.

Semantics:

1. If BFR01 contains the value "04" (Net Change), BFR09 is required.
2. BFR02 is the identifying number for a forecast assigned by the orderer/purchaser.
3. BFR06 is the forecast horizon start date: The date when the forecast horizon (envelope) begins.
4. BFR07 is the forecast horizon end date: The date when the forecast horizon (envelope) ends.
5. BFR08 is the date forecast generated: The date the forecast data was generated.
6. BFR09 is the date forecast updated: The date the forecast was updated with "net change" data. (Used only when data element 353 in BFR01 contains the value "04", meaning net change.)

Loop Name

Pos: 230	Repeat: 200
Mandatory	
Loop: N1	Elements: N/A

User Option (Usage): Used

Purpose: To identify a party by type of organization, name, and code

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
230	N1	Name	O	1		Used
240	N2	Additional Name Information	O	2		Used
250	N3	Address Information	O	2		Used
260	N4	Geographic Location	O	1		Used

N1**Name**

Pos: 230	Max: 1
Heading - Optional	
Loop: N1	Elements: 4

User Option (Usage): Used**Purpose:** To identify a party by type of organization, name, and code**Element Summary:**

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code	M	ID	2/3	Must use
Description: Code identifying an organizational entity, a physical location, property or an individual						
Code List Summary (Total Codes: 1312, Included: 3)						
		<u>Code</u>		<u>Name</u>		
		BT		Bill-to-Party		
		ST		Ship To		
		SU		Supplier/Manufacturer		
N102	93	Name	X	AN	1/60	Must use
Description: Free-form name						
N103	66	Identification Code Qualifier	X	ID	1/2	Must use
Description: Code designating the system/method of code structure used for Identification Code (67)						
Code List Summary (Total Codes: 215, Included: 2)						
		<u>Code</u>		<u>Name</u>		
		91		Assigned by Seller or Seller's Agent		
		92		Assigned by Buyer or Buyer's Agent		
N104	67	Identification Code	X	AN	2/80	Must use
Description: Code identifying a party or other code						

Syntax Rules:

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

N2**Additional Name
Information**

Pos: 240	Max: 2
Heading - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used**Purpose:** To specify additional names or those longer than 35 characters in length**Element Summary:**

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N201	93	Name	M	AN	1/60	Must use
		Description: Free-form name				
N202	93	Name	O	AN	1/60	Used
		Description: Free-form name				

N3**Address Information**

Pos: 250	Max: 2
Heading - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used**Purpose:** To specify the location of the named party**Element Summary:**

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N301	166	Address Information	M	AN	1/55	Must use
		Description: Address information				
N302	166	Address Information	O	AN	1/55	Used
		Description: Address information				

N4 Geographic Location

Pos: 260	Max: 1
Heading - Optional	
Loop: N1	Elements: 4

User Option (Usage): Used

Purpose: To specify the geographic place of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N401	19	City Name	O	AN	2/30	Used
		Description: Free-form text for city name				
N402	156	State or Province Code	O	ID	2/2	Used
		Description: Code (Standard State/Province) as defined by appropriate government agency				
N403	116	Postal Code	O	ID	3/15	Used
		Description: Code defining international postal zone code excluding punctuation and blanks (zip code for United States)				
N404	26	Country Code	O	ID	2/3	Used
		Description: Code identifying the country				

Syntax Rules:

1. C0605 - If N406 is present, then N405 is required.

Comments:

1. A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
2. N402 is required only if city name (N401) is in the U.S. or Canada.

Loop Item Identification

Pos: 010	Repeat: >1
Mandatory	
Loop: LIN	Elements: N/A

User Option (Usage): Must use

Purpose: To specify basic item identification data

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
010	LIN	Item Identification	M	1		Must use
020	UIT	Unit Detail	O	1		Used
450		Loop SDP	O		260	Used
470		Loop SHP	O		25	Used

LIN Item Identification

Pos: 010	Max: 1
Detail - Mandatory	
Loop: LIN	Elements: 7

User Option (Usage): Must use

Purpose: To specify basic item identification data

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
LIN01	350	Assigned Identification	O	AN	1/20	Used
Description: Alphanumeric characters assigned for differentiation within a transaction set						
LIN02	235	Product/Service ID Qualifier	M	ID	2/2	Must use
Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)						
Code List Summary (Total Codes: 477, Included: 1)						
		<u>Code</u> <u>Name</u>				
		BP Buyer's Part Number				
LIN03	234	Product/Service ID	M	AN	1/48	Must use
Description: Identifying number for a product or service						
LIN04	235	Product/Service ID Qualifier	X	ID	2/2	Used
Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)						
Code List Summary (Total Codes: 477, Included: 1)						
		<u>Code</u> <u>Name</u>				
		PO Purchase Order Number				
LIN05	234	Product/Service ID	X	AN	1/48	Used
Description: Identifying number for a product or service						
LIN06	235	Product/Service ID Qualifier	X	ID	2/2	Used
Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)						
Code List Summary (Total Codes: 477, Included: 1)						
		<u>Code</u> <u>Name</u>				
		PD Part Number Description				
LIN07	234	Product/Service ID	X	AN	1/48	Used
Description: Identifying number for a product or service						

Syntax Rules:

1. P0405 - If either LIN04 or LIN05 is present, then the other is required.
2. P0607 - If either LIN06 or LIN07 is present, then the other is required.
3. P0809 - If either LIN08 or LIN09 is present, then the other is required.
4. P1011 - If either LIN10 or LIN11 is present, then the other is required.
5. P1213 - If either LIN12 or LIN13 is present, then the other is required.
6. P1415 - If either LIN14 or LIN15 is present, then the other is required.
7. P1617 - If either LIN16 or LIN17 is present, then the other is required.
8. P1819 - If either LIN18 or LIN19 is present, then the other is required.
9. P2021 - If either LIN20 or LIN21 is present, then the other is required.
10. P2223 - If either LIN22 or LIN23 is present, then the other is required.
11. P2425 - If either LIN24 or LIN25 is present, then the other is required.
12. P2627 - If either LIN26 or LIN27 is present, then the other is required.

13. P2829 - If either LIN28 or LIN29 is present, then the other is required.

14. P3031 - If either LIN30 or LIN31 is present, then the other is required.

Semantics:

1. LIN01 is the line item identification

Comments:

1. See the Data Dictionary for a complete list of IDs.
2. LIN02 through LIN31 provide for fifteen different product/service IDs for each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

UIT

Unit Detail

Pos: 020	Max: 1
Detail - Optional	
Loop: LIN	Elements: 1

User Option (Usage): Used

Purpose: To specify item unit data

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
UIT01	C001	Composite Unit of Measure	M	Comp		Must use
Description: To identify a composite unit of measure (See Figures Appendix for examples of use)						
UIT01-01	355	Unit or Basis for Measurement Code	M	ID	2/2	Must use
Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken						
Code List Summary (Total Codes: 794, Included: 2)						
		<u>Code</u>		<u>Name</u>		
		EA		Each		
		PC		Piece		

Syntax Rules:

1. C0302 - If UIT03 is present, then UIT02 is required.

Loop Ship/Delivery Pattern

Pos: 450	Repeat: 260
Optional	
Loop: SDP	Elements: N/A

User Option (Usage): Used

Purpose: To identify specific ship/delivery requirements

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
450	SDP	Ship/Delivery Pattern	O	1		Used
460	FST	Forecast Schedule	O	260		Used

SDP Ship/Delivery Pattern

Pos: 450	Max: 1
Detail - Optional	
Loop: SDP	Elements: 2

User Option (Usage): Used

Purpose: To identify specific ship/delivery requirements

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SDP01	678	Ship/Delivery or Calendar Pattern Code	M	ID	1/2	Must use
Description: Code which specifies the routine shipments, deliveries, or calendar pattern All valid standard codes are used. (Total Codes: 44)						
SDP02	679	Ship/Delivery Pattern Time Code	M	ID	1/1	Must use
Description: Code which specifies the time for routine shipments or deliveries All valid standard codes are used. (Total Codes: 9)						

Comments:

1. The intent of this segment is to define the routine ship or delivery patterns, as required, when order quantities are in "buckets", such as weekly, monthly. Ship/delivery patterns eliminate the need to transmit discrete quantities and dates for each required shipment or delivery. It is assumed that a "bucketed" quantity is to be divided equally by the ship/delivery pattern. For example, a weekly quantity of 100 with a delivery pattern of Monday and Wednesday would result in 50 to be delivered on Monday and 50 to be delivered on Wednesday.

FST Forecast Schedule

Pos: 460	Max: 260
Detail - Optional	
Loop: SDP	Elements: 4

User Option (Usage): Used

Purpose: To specify the forecasted dates and quantities

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
FST01	380	Quantity	M	R	1/15	Must use
		Description: Numeric value of quantity				
FST02	680	Forecast Qualifier	M	ID	1/1	Must use
		Description: Code specifying the sender's confidence level of the forecast data or an action associated with a forecast				
		All valid standard codes are used. (Total Codes: 21)				
FST03	681	Forecast Timing Qualifier	M	ID	1/1	Must use
		Description: Code specifying interval grouping of the forecast				
		All valid standard codes are used. (Total Codes: 11)				
FST04	373	Date	M	DT	8/8	Must use
		Description: Date expressed as CCYYMMDD				

Syntax Rules:

1. P0607 - If either FST06 or FST07 is present, then the other is required.
2. P0809 - If either FST08 or FST09 is present, then the other is required.

Semantics:

1. If FST03 equals "F" (indicating flexible interval), then FST04 and FST05 are required. FST04 would be used for the start date of the flexible interval and FST05 would be used for the end date of the flexible interval.

Comments:

1. As qualified by FST02 and FST03, FST04 represents either a discrete forecast date, the first date of a forecasted bucket (weekly, monthly, quarterly, etc.) or the start date of a flexible interval.
2. FST06 qualifies the time in FST07. The purpose of the FST07 element is to express the specific time of day in a 24-hour clock to satisfy "just-in-time" requirements. As an alternative, the ship/delivery pattern segment (SDP) may be used to define an approximate time, such as a.m. or p.m.

Loop Shipped/Received Information

Pos: 470	Repeat: 25
Optional	
Loop: SHP	Elements: N/A

User Option (Usage): Used

Purpose: To specify shipment and/or receipt information

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
470	SHP	Shipped/Received Information	O	1		Used

SHP Shipped/Received Information

Pos: 470	Max: 1
Detail - Optional	
Loop: SHP	Elements: 4

User Option (Usage): Used

Purpose: To specify shipment and/or receipt information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SHP01	673	Quantity Qualifier	O	ID	2/2	Used
		Description: Code specifying the type of quantity All valid standard codes are used. (Total Codes: 832)				
SHP02	380	Quantity	X	R	1/15	Used
		Description: Numeric value of quantity				
SHP03	374	Date/Time Qualifier	X	ID	3/3	Used
		Description: Code specifying type of date or time, or both date and time All valid standard codes are used. (Total Codes: 1112)				
SHP04	373	Date	X	DT	8/8	Used
		Description: Date expressed as CCYYMMDD				

Syntax Rules:

1. C0102 - If SHP01 is present, then SHP02 is required.
2. L030405 - If SHP03 is present, then at least one of SHP04 or SHP05 is required.
3. C0403 - If SHP04 is present, then SHP03 is required.
4. C0503 - If SHP05 is present, then SHP03 is required.

Semantics:

1. SHP04 is the date shipped, delivered, received, or the cumulative quantity start date (as qualified by SHP03).
2. SHP06 is the cumulative quantity end date.

Comments:

1. The SHP segment is used to communicate shipment, delivery, or receipt information and may include discrete or cumulative quantities, dates, and times.
2. If SHP01 equals "02", "07", "08", "09", or "10" (indicating cumulative quantities), then SHP04 and SHP06 are required to identify the start and end dates of the quantity count.

CTT Transaction Totals

Pos: 010	Max: 1
Summary - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Used

Purpose: To transmit a hash total for a specific element in the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTT01	354	Number of Line Items	M	N0	1/6	Must use

Description: Total number of line items in the transaction set

CTT02	347	Hash Total	O	R	1/10	Used
-------	-----	------------	---	---	------	------

Description: Sum of values of the specified data element. All values in the data element will be summed without regard to decimal points (explicit or implicit) or signs. Truncation will occur on the left most digits if the sum is greater than the maximum size of the hash total of the data element. Example: -.0018 First occurrence of value being hashed. .18 Second occurrence of value being hashed. 1.8 Third occurrence of value being hashed. 18.01 Fourth occurrence of value being hashed. ----- 1855 Hash total prior to truncation. 855 Hash total after truncation to three-digit field.

Syntax Rules:

1. P0304 - If either CTT03 or CTT04 is present, then the other is required.
2. P0506 - If either CTT05 or CTT06 is present, then the other is required.

Comments:

1. This segment is intended to provide hash totals to validate transaction completeness and correctness.

SE**Transaction Set Trailer**

Pos: 020	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use**Purpose:** To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)**Element Summary:**

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	Number of Included Segments	M	N0	1/10	Must use
Description: Total number of segments included in a transaction set including ST and SE segments						
SE02	329	Transaction Set Control Number	M	AN	4/9	Must use
Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set						

Comments:

1. SE is the last segment of each transaction set.

EDI Sample

ISA*00* *00* *ZZ*0123456789 *ZZ*DKEUS
 *220806*1316*U*00401*000000160*0*P*^~
 GS*PS*0123456789*123456789*20220806*1316*160*X*004010~
 ST*830*0002~
 BFR*05*123LINE**DL*A*20220101*20231001*20220805~
 N1*SU*DIGI-KEY CORP.*92*23648~
 N1*ST*PLANT #7 SAMPLE CO*92*PLT 07~
 N3*DIV PRIMARY*100 GREEN AVE~
 N4*MIAMI*FL*12345~
 N1*BT*BILL CO*~
 N3*P.O. BOX 174*FLOOR 2~
 N4*THE LAKES*WI*549361337~
 LIN**BP*8M0053411*PO*P855378-A*PD*100PF CAPACITOR~
 UIT*PC~
 SDP*A*A~
 FST*100000*C*D*20221005~
 FST*96000*C*D*20221116~
 FST*88000*D*M*20230125~
 FST*92000*D*M*20230322~
 FST*56000*D*M*20230517~
 FST*12000*D*M*20230719~
 SHP*01*72000*050*20220715~
 SHP*02*320000*051*20220101**20220805~
 LIN**BP*8M0053415*PO*P855846-A*PD*ALUM ELECTROLYTIC CAPACITOR~
 UIT*PC~
 SDP*A*A~
 FST*10000*C*D*20230104~
 FST*30000*C*D*20230118~
 FST*10000*C*D*20230322~
 FST*17000*C*D*20230329~
 FST*8000*D*D*20230426~
 FST*5000*D*M*20230614~
 FST*1000*D*M*20230719~
 FST*1000*D*M*20230823~
 SHP*01*0*050*20220101~
 SHP*02*0*051*20220101**20220805~
 LIN**BP*8M0053651*PO*P855387-A*PD*+1K OHM RESISTOR~
 UIT*PC~
 SDP*A*A~
 FST*4000*C*D*20221213~
 FST*4000*D*M*20231025~
 SHP*01*6000*050*20220520~
 SHP*02*6000*051*20220101**20220805~
 LIN**BP*8M0053919*PO*P855595-B*PD*+DUAL CHANNEL ISOLATOR~
 UIT*PC~
 SDP*A*A~
 FST*6595*C*D*20220905~
 FST*5000*D*M*20231003~
 SHP*01*905*050*20220713~
 SHP*02*905*051*20220101**20220805~
 LIN**BP*8M0061747*PO*P855424-B*PD*+DIFFERENTIAL LINE DRIVER~
 UIT*PC~
 SDP*A*A~
 FST*0*C*D*20220805~
 SHP*01*5000*050*20220520~
 SHP*02*7500*051*20220101**20220805~
 LIN**BP*8M0068738*PO*P855705-B*PD*+CAPACITOR-10UF,50V,20%~
 UIT*PC~

Digi-Key EDI 830 Delivery Forecast

20

SDP*A*A~
FST*1000*C*D*20230104~
FST*1000*C*D*20230412~
SHP*01*0*050*20220101~
SHP*02*0*051*20220101**20220805~
LIN**BP*8M0075092*PO*P855425-A*PD*+75 OHM RESISTOR~
UIT*PC~
SDP*A*A~
FST*10000*C*D*20221012~
FST*5000*C*D*20221109~
FST*5000*C*D*20221207~
FST*5000*C*D*20230208~
FST*5000*C*D*20230419~
FST*5000*C*D*20230614~
FST*10000*D*D*20230816~
FST*10000*D*D*20240103~
SHP*01*15000*050*20220715~
SHP*02*15000*051*20220101**20220805~
CTT*53*3416395~
SE*563*0002~
GE*2*160~
IEA*1*000000160~